

BRIAN SANDOVAL
Governor
JOAN LAMBERT
Chair, Nevada Tax Commission
DEONNE E. CONTINE
Executive Director

STATE OF NEVADA DEPARTMENT OF TAXATION

Web Site: http://tax.nv.gov

1550 College Parkway, Suite 115 Carson City, Nevada 89706-7937 Phone: (775) 684-2000 Fax: (775) 684-2020

LAS VEGAS OFFICE
Grant Sawyer Office Building, Suite1300
555 E. Washington Avenue
Las Vegas, Nevada 89101
Phone: (702) 486-2300 Fax: (702) 486-2373

RENO OFFICE 4600 Kietzke Lane Building L, Suite 235 Reno, Nevada 89502 Phone: (775) 687-9999 Fax: (775) 688-1303

HENDERSON OFFICE 2550 Paseo Verde Parkway, Suite 180 Henderson, Nevada 89074 Phone: (702) 486-2300 Fax: (702) 486-3377

In the Matter of:	
Approval of the 2017-201	8
Rural Building Manual	

NOTICE OF DECISION

Appearances

Terry Rubald, Deputy Executive Director of the Division of Local Government Services, appeared on behalf of the Department of Taxation.

Summary

The matter of the approval of the 2017-2018 Rural Building Costs Manual came before the Nevada Tax Commission (Commission) for hearing in Carson City, Nevada, on March 10, 2015, after due notice to each Assessor. The Commission reviewed the Rural Building Costs Manual and the report of the Department.

DECISION

The Commission, having considered all evidence and testimony pertaining to the matter, hereby adopts the 2017-2018 Rural Building Costs Manual listing costs without adjustment for unskilled labor as reported by the Department for use by county assessors pursuant to NAC 361.128(2).

BY THE NEVADA TAX COMMISSION THIS DAY OF MARCH, 2016.

Deonne Contine, Executive Director

cc: County Assessors

Gina Session, Chief Deputy Attorney General



NEVADA DEPARTMENT OF TAXATION

Division of Local Government Services

2017-2018

ASSESSOR'S HANDBOOK OF RURAL BUILDING COSTS

DATE OF VALUATION JANUARY 1, 2016

2017-201

Rural Building Cost Manual

Department of Taxation
Division of Local Government Services
1550 E. College Parkway, Suite 115
Carson City, NV 89706
Phone 775.684.2100 • Fax 775.684.2020

INSTRUCTIONS FOR USE

The Rural Building Manual (RBM) is intended to be an assessment tool used to standardize and streamline improvement valuations for rural properties. It provides a broad listing of structures and improvements which are customarily found in rural areas; moreover, it includes photos and descriptions which may be useful to assessors when classifying improvement quality or computing segregated costs.

Based on current construction practices, all RBM sections report costs found in the Marshall and Swift Cost Manual <u>absent of any adjustments for unskilled farm labor</u>. As such, <u>assessors will not adjust values upward</u> by 33 percent as authorized by NAC 361.128 paragraph 3(b). However, to account for the use of unskilled farm labor in the construction of improvements, <u>assessors may make downward adjustments</u> of 25 percent when appropriate.

All photos contained in the RBM are to be used as a guide to help determine quality, class and style of buildings. Photos are not to be used as a method for determination of whether a building should be valued using the RBM.

If the RBM or the Marshall Swift Cost Manual does not contain costs for a particular kind of structure or improvement, the county assessor may apply to the Executive Director for permission to use alternative recognized cost manuals, cost determinations or subscription services.



CONTENTS

2017-18 RURAL BUILDING COST MANUAL

BASIC FARM BUILDINGS – SECTION 1	
GENERAL PURPOSE BARNS	1
HAY STORAGE BARNS	5
FEED BARNS	
POLE BARNS	9
SHOPS	13
MACHINERY AND EQUIPMENT SHEDS	15
SMALL SHEDS AND PUMP HOUSES	17
GENERAL PURPOSE BUILDINGS	19
ROOT CELLARS	22
COLD STORAGE WALK-IN BOXES – POTATO STORAGE	23
STEEL BUILDINGS – FARM AND RANCH	26
STEEL BUILDINGS – ADDITIONAL FEATURES	28
PREFABRICATED METAL HORSE STABLES	29
DAIRY BARNS - SECTION 2	
DAIRY BARNS - MILKING PARLORS	1
MILK STORAGE, WASH AND EQUIPMENT ROOMS	
WASH PEN AND HOLDING AREA	
DAIRY EQUIPMENT	9
BUNK HOUSES – SECTION 3	
BUNK HOUSES	1
UTILITIES – SECTION 4	
DOMESTIC WATER SYSTEMS	
SEPTIC SYSTEMS	
MOBILE HOME HOOKUPS	
CORRALS AND FENCES – SECTION 5	
WOOD, METAL AND WIRE FENCING, FEED TROUGHS, CONCRETE FLATWORK ANI	O WALLS1
CHAIN LINK FENCING AND GATES	
LOADING CHUTES AND DIPPING VATS	
CATTLE GUARDS, CATTLE SQUEEZE, AND WINDMILLS	
CATTLE AND HORSE WATERING TANKS	
COMMERCIALLY MANUFACTURED METAL FENCE PANELS AND CATTLE HANDLIN	G EQUIPMENT11

MISCELLANEOUS COSTS - SECTION 6

	FARM SILOS	1
	STEEL GRAIN BINS	3
	FEED TANKS AND GRAIN HANDLING SYSTEMS	4
	ELECTRIC POWER PLANTS	6
	LIVESTOCK SCALES, SCALE CAGES AND MOTOR TRUCK SCALES	7
	UNDER AND ABOVE GROUND FUEL STORAGE AND FUEL DISPENSERS	9
	PREFABRICATED TELECOM / COMMUNICATION EQUIPMENT SHELTERS	11
C	OMPUTATIONAL TABLES - SECTION 7	
	MEASUREMENT PRINCIPLES	1
	WEIGHTS AND MESURES	1
	METRIC MEASURE	1
	LINEAR MEASURE	1
	SURVEYOR'S MEASURE	1
	SQUARE MEASURE	2
	CUBIC MEASURE	2
	ANGLES AND ARCS	2
	BOARD MEASURE	2
	AREAS	3
	MEASURES AND THEIR EQUIVALENTS	3
	WEIGHTS - BRICK AND LIME	4
	MISCELLANEOUS WEIGHT AND MEASURE EQUIVALENTS	.4
	AREAS AND MEASUREMENTS	5
	COUNTY ALLOCATION TABLES	
	TABLE FOR AREA AND CAPACITY OF CIRCULAR TANKS	6
	TABLE FOR CONVERSION OF LINEAR INTO BOARD FEET	7
	BOARD MEASURE	7
	CENTER PIVOT IRRIGATION SYSTEM DATA	8

2017-2018 RURAL BUILDING COST MANUAL

Section 1

BASIC FARM BUILDINGS

METAL BARNS



LOW QUALITY



AVERAGE QUALITY



PHOTOS COURTESY OF CHURCHILL COUNTY ASSESSOR

WOOD BARNS



LOW QUALITY



AVERAGE QUALITY




PHOTOS COURTESY OF CHURCHILL COUNTY ASSESSOR

BASIC FARM BUILDINGS GENERAL PURPOSE BARNS



LOW QUALITY



AVERAGE QUALITY



GENERAL PURPOSE BARNS

	CLASS 1	CLASS 2	CLASS 3
COMPONENT	LOW QUALITY	AVERAGE QUALITY	GOOD QUALITY
Foundation	Perimeter concrete and column	Perimeter concrete and column	Perimeter concrete and column
	footings	footings	footings
Floor	Dirt	Dirt	Dirt
Wall Structure	Light wood boxed frame or wood posts and beams, 10' eave height	Average 2"x 4", 24" on center, 10' eave height	Concrete block or good 2"x 4", 16" on center or 2"x 6", 24" on center, 10' eave height
Exterior Wall Cover	Light wood siding board and batten or light aluminum siding	Average wood or aluminum siding	Good wood siding painted or standard gauge corrugated iron or aluminum siding
Roof Construction	Medium pitch, 2"x 4" rafters 24" to 36" on center, composition decking	Medium pitch, wood joists, wood or composition decking	Medium pitch, wood joists, wood or composition decking
Roof Cover	Composition shingle, asphalt roll paper or light wood shingles	Good wood shingles, light aluminum or corrugated iron	Standard gauge aluminum or corrugated iron or good wood shingles
Electrical	Minimal per class	Minimal per class	Minimal per class
Plumbing	Minimal per class	Minimal per class	Minimal per class

Includes normal stalls commensurate with quality class.

SQUARE FOOT COSTS


CLASS	1,000	2,000	3,000	4,000	5,000	6,000	7,000	8,000	9,000	10,000	11,000
1	\$ 23.08	19.28	17.72	16.93	16.45	16.14	15.89	15.46	15.18	14.87	14.51
2	33.35	27.60	25.10	23.89	23.18	22.74	22.39	21.76	21.25	20.72	20.26
3	41.69	36.95	34.46	33.13	32.44	31.93	31.60	30.95	30.43	29.88	29.49

ADD Concrete or wood floors, or concrete flatwork per square foot: \$ 4.07

Lofts per square foot of floor area Low Quality: \$ 4.91

Average Quality: 6.44 Good Quality: 8.45

BASIC FARM BUILDINGS HAY STORAGE BARNS



AVERAGE QUALITY



GOOD QUALITY

HAY STORAGE BARNS

	CLASS 1	CLASS 2	CLASS 3		
COMPONENT	LOW QUALITY	AVERAGE QUALITY	GOOD QUALITY		
Foundation	Redwood or cedar mudsills	Concrete or masonry piers	Continuous concrete		
Floor	Dirt	Dirt	Dirt		
Wall Structure	Light wood boxed frame or wood posts and beams, 10' eave height	Average 2"x 4", 24" on center, 10' eave height	Good 2"x 4", 16" on center or 2"x 6", 24" on center, 10' eave height		
Exterior Wall Cover	Light wood siding, board and batten or light aluminum siding	Average wood or aluminum siding	Good wood siding painted, standard gauge corrugated iron or aluminum siding		
Roof Construction	Medium to high pitch 2"x 4" rafters 24" to 36" on center, or light wood trusses	Medium to high pitch, average wood trusses	Medium to high pitch, good wood trusses		
Roof Cover	Composition shingle, asphalt roll paper or light wood shingles	Good wood shingles, light aluminum or corrugated iron	Standard gauge aluminum, corrugated iron or good wood shingles		
Electrical	Minimal per class	Minimal per class	Minimal per class		
Plumbing	Minimal per class	Minimal per class	Minimal per class		

SQUARE FOOT COSTS

CLASS	1,000	2,000	3,000	4,000	5,000	6,000	7,000	8,000	9,000	10,000	11,000
1	\$ 21.42	17.58	16.04	15.23	14.84	14.43	14.24	13.78	13.50	13.19	12.99
2	30.22	24.20	21.41	20.26	19.47	18.54	18.31	17.54	16.94	16.27	15.94
3	41.37	33.42	30.08	28.06	27.32	26.41	25.89	24.92	24.24	23.30	22.71

ADD Concrete or wood floors, or concrete flatwork per square foot: \$ 4.07


Lofts per square foot of floor area Low Quality: \$ 4.91

Average Quality: 6.44 Good Quality: 8.45

FEED BARNS



AVERAGE QUALITY



INTERIOR DETAIL



FEED BARNS

	CLASS 1	CLASS 2	CLASS 3		
COMPONENT	LOW QUALITY	AVERAGE QUALITY	GOOD QUALITY		
Foundation	Redwood or cedar mudsills	Concrete or masonry piers	Continuous concrete		
Floor	Dirt	Dirt	Dirt		
Wall Structure	Light wood frame, 10' eave height	Average wood frame, 10' eave height	Good wood frame, 10' eave height		
Exterior Wall Cover	Closed sides and open ends	Partially open sides, standard corrugated iron or average wood siding on ends	Partially open sides, good quality siding		
Roof Construction	Medium to low pitch 2"x 4" rafters 24" to 36" on center, or light wood trusses	Medium to low pitch, average wood trusses	Medium to low pitch, good wood trusses		
Roof Cover	Light metal or composition shingle	Standard gauge corrugated metal	Wood shingles		
Electrical	Minimal per class	Minimal per class	Minimal per class		
Plumbing	Minimal per class	Minimal per class	Minimal per class		

Includes normal feed stalls commensurate with quality class.

SQUARE FOOT COSTS


CLASS	1,000	2,000	3,000	4,000	5,000	6,000	7,000	8,000	9,000	10,000	11,000
1	\$ 14.46	13.41	12.83	12.45	12.30	12.22	12.14	12.07	12.01	11.93	11.91
2	17.66	16.66	15.99	15.46	15.13	14.99	14.88	14.79	14.69	14.62	14.60
3	23.49	22.55	21.77	21.15	20.60	20.28	20.12	20.02	19.95	19.76	19.66

ADD Concrete or wood floors, or concrete flatwork per square foot: \$ 4.07

Lofts per square foot of floor area Low Quality: \$ 4.91

Average Quality: 6.44
Good Quality: 8.45

POLE BARNS



AVERAGE QUALITY – ALL SIDES OPEN WOODEN POLES – WOOD FRAME



GOOD QUALITY – ALL SIDES OPEN STEEL POLES, STEEL TRUSS & STEEL FRAME

POLE BARNS - AVERAGE QUALITY

Structure	Poles 15' to 20' on center
Floor	Dirt - use square foot additive for concrete
Roof	Average wood trusses or average steel trusses, low pitch, corrugated iron or aluminum cover, gable end enclosed, 2' overhang on 2 sides
Walls	18' wall height, average wood frame or average prefabricated steel frame with corrugated iron covering where called for

All costs listed are based on average quality materials. Use multiplier for good quality materials--heavy steel frame and trusses, wide span, heavy gauge roof cover. Use multiplier for low quality materials--light wood poles and frame with light wood or steel trusses and light gauge roof cover.

SQUARE FOOT COSTS

TYPE "A" (ALL SIDES OPEN)

END SIDE LENGTH

WIDTH	34'	51'	68'	85'	102'	119'	136'	153'	170'	187'
20'	\$ 11.92	11.55	11.19	10.88	10.88	10.48	10.48	10.48	10.48	10.48
25'	11.19	10.88	10.48	10.19	9.83	9.83	9.83	9.83	9.83	9.83
30'	10.67	10.45	10.19	9.78	9.49	9.49	9.49	9.49	9.49	9.49
35'	10.48	10.15	9.81	9.47	9.12	9.12	9.12	9.12	9.12	9.12
40'	10.42	10.13	9.74	9.44	9.10	9.10	9.10	9.10	9.10	9.10
45'	10.37	10.00	9.66	8.67	8.64	8.64	8.64	8.64	8.64	8.64
50'	10.34	9.97	9.57	8.58	8.45	7.23	7.23	7.23	7.23	7.23
60'	10.31	9.94	9.41	8.22	8.19	7.09	7.09	7.09	7.09	7.09
70'	10.13	9.78	9.04	7.93	7.76	6.94	6.94	6.94	6.94	6.94
80'	10.13	9.78	8.67	7.76	7.47	6.77	6.77	6.77	6.77	6.77

ADD Concrete or wood floors, or concrete flatwork per square foot: \$ 4.07

QUALITY MULTIPLIERS Good Quality: 1.26

Low Quality: 0.69

POLE BARNS - AVERAGE QUALITY

SQUARE FOOT COSTS

TYPE "B" (ENDS AND ONE SIDE CLOSED - ONE SIDE OPEN)

END

SIDE LENGTH

WIDTH	34'	51'	68'	85'	102'	119'	136'	153'	170'	187'
20'	\$ 17.28	15.75	14.96	14.56	14.24	13.94	13.79	13.76	13.73	13.54
25'	15.97	14.56	13.73	13.28	13.06	12.55	12.45	12.26	12.16	12.10
30'	15.23	13.76	13.06	12.51	12.29	12.05	11.89	11.67	11.60	11.55
35'	14.72	13.14	12.45	11.92	11.67	11.58	11.25	11.22	11.19	11.14
40'	14.37	12.77	12.07	11.60	11.52	11.19	10.88	10.85	10.80	10.71
45'	14.19	12.48	11.70	11.22	10.93	10.71	10.48	10.45	10.42	10.37
50'	14.02	12.16	11.65	10.82	10.71	10.45	10.23	10.19	10.08	10.03
60'	13.71	12.07	11.14	10.51	10.42	10.19	10.00	9.89	9.76	9.71
70'	13.51	11.81	10.82	10.45	10.23	10.03	9.76	9.71	9.63	9.60
80'	13.14	11.62	10.45	10.29	10.03	9.71	9.57	9.54	9.49	9.41

ADD Concrete or wood floors, or concrete flatwork per square foot : \$ 4.07

QUALITY MULTIPLIERS Good Quality: 1.26

Low Quality: 0.69

SQUARE FOOT COSTS

TYPE "C" (ALL SIDES CLOSED)

END

SIDE LENGTH

WIDTH	34'	51'	68'	85'	102'	119'	136'	153'	170'	187'
20'	\$ 19.60	18.21	17.44	16.99	16.82	16.56	16.42	16.37	16.34	16.21
25'	17.62	16.34	15.57	15.15	14.87	14.67	14.58	14.34	13.97	13.79
30'	16.56	14.79	14.13	13.60	13.42	13.09	12.96	12.85	12.83	12.74
35'	15.63	14.00	13.60	13.01	12.91	12.53	12.43	12.40	12.18	12.16
40'	15.15	13.68	12.98	12.55	12.45	12.13	12.05	11.81	11.70	11.65
45'	14.67	13.14	12.45	12.13	11.70	11.58	11.41	11.28	11.25	11.22
50'	14.24	12.83	11.95	11.81	11.67	11.25	11.22	11.19	11.07	10.99
60'	13.73	12.40	11.55	11.01	10.90	10.56	10.48	10.34	10.26	10.19
70'	13.42	12.05	11.28	10.85	10.53	10.31	10.13	10.11	10.00	9.97
80'	12.94	11.60	10.85	10.42	10.13	9.83	9.78	9.68	9.60	9.46

ADD Concrete or wood floors, or concrete flatwork per square foot: \$ 4.07

QUALITY MULTIPLIERS Good Quality: 1.26

Low Quality: 0.69

SIDE SHEDS - AVERAGE QUALITY

Structure	1 row of poles 15' to 20' on center, 1 side ties into adjoining building
Floor	Dirt - Use square foot additive for concrete
Roof	Light wood trusses, low pitch, corrugated iron or aluminum cover, ends enclosed, 2' overhang on 1 side
Walls	14' to 16' wall height, light wood frame with corrugated iron covering

SQUARE FOOT COSTS

WITH OPEN SIDES: \$ 6.98 TO \$ 9.22 WITH ENCLOSED SIDES: 10.07 TO 13.29

ADD Concrete or wood floors, or concrete flatwork per square foot: \$ 4.07

BASIC FARM BUILDINGS SHOPS



AVERAGE QUALITY



GOOD QUALITY



GOOD QUALITY – CLASS S

SHOPS

	CLASS 1	CLASS 2	CLASS 3
COMPONENT	LOW QUALITY	AVERAGE QUALITY	GOOD QUALITY
Foundation	Light concrete	Standard concrete	Standard concrete
Floor	Concrete	Concrete	Concrete
Wall Structure	Light wood frame, 15' eave height	Average wood frame, 15' eave height	Good wood frame 15' eave height
Exterior Wall Cover	Light metal or low cost boards	Standard gauge corrugated metal or average wood siding	Good wood siding painted or C-block
Roof Construction	Low to medium pitch, 2"x 4" rafters 24" to 36" on center or light wood trusses	Low to medium pitch, average wood trusses	Low to medium pitch, good wood trusses
Roof Cover	Light metal	Standard gauge metal	Wood shingles
Electrical	2 outlets per 1,000 square foot	4 outlets per 1,000 square foot	4 outlets per 1,000 square foot
Plumbing	1 cold water outlet	2 cold water outlets	1 rough fixture plus 2 cold water outlets
Doors	1 light sliding or swinging door per 2,000 square foot	1 average sliding or swinging door per 2,000 square foot	1 drive through door per 1,000 square foot plus 1 walk-through door
Windows	None	None or few low cost	5 percent of wall area
Shape	Square or rectangular length between 1 and 2 times width	Square or rectangular length between 1 or 2 times width	Square or rectangular length between 1 and 2 times width

SQUARE FOOT COSTS

CLASS	500	1,000	1,500	2,000	2,500	3,000	4,000	5,000	6,000	8,000
1	\$ 24.55	22.95	21.48	20.60	19.90	19.40	18.68	18.08	17.73	17.28
2	35.90	31.78	27.94	27.10	25.44	24.63	23.57	22.87	22.16	21.51
3	45.77	37.65	37.06	34.86	33.36	32.11	30.43	29.63	28.59	27.61

ADD For interior finish - Class 1: \$ 1.66 per square foot of floor area Class 2: 2.05 per square foot of floor area

Class 3: 2.53 per square foot of floor area

MACHINERY & EQUIPMENT SHEDS



AVERAGE QUALITY



AVE. QUALITY – 1 SIDE OPEN



GOOD QUALITY



GOOD QUALITY – 1 SIDE OPEN

MACHINERY AND EQUIPMENT SHEDS

	CLASS 1	CLASS 2	CLASS 3
COMPONENT	LOW QUALITY	AVERAGE QUALITY	GOOD QUALITY
Foundation	Light perimeter concrete	Concrete perimeter	Concrete perimeter
Floor	Dirt	Dirt or concrete*	Dirt or concrete*
Wall Structure	Light wood boxed frame or post and beam, 10' eave height	Post and beam construction, 10' eave height	Average 2"x 4", 24" on center, 10' eave height
Exterior Wall Cover	Light wood or metal siding on a wood frame	Average wood or metal siding on wood frame	Good wood or metal siding on wood frame
Roof Construction	Shed type, or low pitch open wood system for metals	Low pitch, open wood system for metals or wood shingles	Medium pitch, open wood system for metals or wood shingles
Roof Cover	Corrugated metal	Corrugated metal or wood shingle	Standard gauge metal or good wood shingles
Electrical	None	2 outlets per 1,000 square foot	4 outlets per 1,000 square feet
Plumbing	None	None	None
Shape	Usually elongated, width between 15 and 30 feet, any length	Usually elongated, width between 15 and 30 feet, any length	Usually elongated, width between 15 and 30 feet, any length

SQUARE FOOT COSTS

TYPE I (ALL SIDES CLOSED)

CLASS	500	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	5,000	6,000
1	\$ 16.99	13.68	12.58	12.04	11.80	10.95	10.91	10.65	10.55	10.44	10.33
2	23.77	19.50	18.24	17.55	17.18	16.05	15.94	15.69	15.52	15.47	15.30
3	32.72	27.65	26.11	25.30	24.93	23.53	23.29	23.08	22.87	22.79	22.51

TYPE II (ONE SIDE OPEN)

CLASS	500	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	5,000	6,000
1	\$ 13.96	11.17	10.26	9.75	9.43	8.88	8.81	8.62	8.48	8.46	8.35
2	19.71	16.31	15.05	14.40	14.04	13.45	13.22	13.06	12.83	12.80	12.64
3	28.35	23.65	22.08	21.86	21.40	20.58	20.31	20.11	19.76	19.65	19.45

ADD Concrete or wood floors, or concrete flatwork per square foot:


\$ 4.07

SMALL SHEDS AND PUMP HOUSES



LOW QUALITY











SMALL SHEDS AND PUMP HOUSES

	CLASS 1	CLASS 2	CLASS 3
COMPONENT	LOW QUALITY	AVERAGE QUALITY	GOOD QUALITY
Foundation	Redwood or cedar mudsills	Concrete or masonry piers	Continuous concrete
Floor	Dirt	Dirt*	Dirt*
Wall Structure	Light wood boxed frame or wood	Average 2"x 4" on center, 8'	Good 2"x 6", 24" on center, or
	posts and beams 8' eave height	eave height	2"x 4", 16" on center, 8' eave
		-	height
Exterior Wall Cover	Light wood siding, board and	Average wood or aluminum	Good wood siding painted,
	batten or light aluminum siding	siding	standard gauge corrugated or
			aluminum siding
Roof Construction	Low to medium pitch, shed type,	Low to medium pitch, gable or	Low to medium pitch, gable or
	light wood framing	shed type, average wood	shed type, good wood framing
		framing	31 13
Roof Cover	Composition shingle asphalt roll	Good shingles light aluminum	Standard gauge, aluminum
	paper, light wood shingles or	corrugated iron	corrugated iron or good wood
	sod		shakes
Electrical	None	Minimal	Minimal
Plumbing	None	None	None

NOTE: Type II with 2 sides open; reduce cost by an additional 12 percent. Type II with 3 sides open; reduce cost by an additional 25 percent. Type II with 4 sides open; reduce cost by an additional 30 percent.

SQUARE FOOT COSTS

TYPE I (ALL SIDES CLOSED)

•	CLASS	30	50	60	80	100	120	150	200	250	300	400	500
	1	\$ 23.22	19.30	18.74	16.82	15.67	14.94	14.16	12.93	12.43	11.91	11.15	10.70
	2	29.37	26.20	24.50	22.45	21.21	20.41	19.53	18.27	17.69	17.11	16.31	15.85
ĺ	3	46.90	38.22	36.84	33.40	30.20	28.58	26.87	24.87	23.07	21.91	20.28	19.24

TYPE II (ONE SIDE OPEN)

CLASS	30	50	60	80	100	120	150	200	250	300	400	500
1	\$ 19.33	15.75	14.57	13.63	13.05	12.35	11.60	11.07	10.70	10.24	9.77	9.35
2	26.48	22.64	21.81	19.28	17.69	16.26	15.71	14.81	14.59	13.46	12.77	12.14
3	36.22	32.64	29.96	26.64	24.61	22.81	22.10	21.04	20.00	18.94	18.08	17.30


ADD Concrete or wood floors, or concrete flatwork per square foot: \$ 4.07
Fiberglass Roll or Batt Insulation: 0.74
Gypsum Board Interior: 1.60

GENERAL PURPOSE BUILDINGS

General purpose buildings adapt easily to many different uses, especially as garages, machine repair shops, or storage areas. General purpose buildings may also function as feed storage sheds or livestock shelters.

General purpose buildings typically employ simple designs that emphasize maximum utility at minimum cost.

CLASS ILLUSTRATIONS



GENERAL PURPOSE BUILDINGS

	CLASS 1	CLASS 2	CLASS 3
COMPONENT	LOW QUALITY	AVERAGE QUALITY	GOOD QUALITY
Foundation	Wood girder on masonry piers; or holes and backfill for pole frame	Holes and backfill for pole frame; or light perimeter foundation	Continuous concrete poured with floor
Floor	Dirt	Concrete	Concrete
Frame and Exterior Walls	Eave height 8'. Pole or box frame with metal exterior or low grade sidings	Eave height 8'. Pole or box frame with metal exterior or average grade sidings	Eave height 8'. Conventional wood stud frame with good wood or metal sidings
Interior Walls	Normally unfinished see options	Normally unfinished see options	Normally unfinished see options
Roof Structure	Low pitch wood system for metal or low cost composition roof	Low to medium pitch wood system for average cost metal or composition roof	Medium pitch wood system with composition or wood sheathing
Roof Cover	Aluminum or steel corrugated or crimped, low quality	Aluminum or steel corrugated or crimped, average quality	Composition shingle, good quality or average quality metal or wood shingles
Electrical	None	Minimal	Minimal
Plumbing	None	None	None

SQUARE FOOT COSTS

CLASS	500	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500
1	\$ 13.63	11.65	11.12	10.52	10.27	9.89	9.64	9.51	9.41
2	19.39	17.06	16.37	15.62	15.34	14.88	14.57	14.43	14.28
3	25.61	22.72	21.91	21.62	20.66	20.09	19.70	19.50	19.39

ADD For interior finish - Class 1: \$ 1.62 per square foot of floor area Class 2: 1.78 per square foot of floor area

Class 3: 1.94 per square foot of floor area

Height adjustment:

Add 2 percent for each foot of average story height over 8' base height. Subtract 2 percent for each foot of average story height under 8' base height.

ROOT CELLARS

	CLASS 1	CLASS 2	CLASS 3
COMPONENT	LOW QUALITY	AVERAGE QUALITY	GOOD QUALITY
Foundation	Cedar or redwood mudsills or rubble	Concrete or masonry footings	Continuous concrete
Floor	Dirt	Dirt	Concrete
Wall Structure	Post and beams with wood siding	Post and beams with wood siding	Concrete block or poured concrete
Roof Construction	Flat or low to medium pitch gable, poles or light wood	Flat or low to medium pitch gable, lodge pole or heavier wood	Flat reinforced poured concrete
Roof Cover	Sod	Sod, or if above ground corrugated metal with inside insulation	Sod, or if above ground corrugated metal with inside insulation
Electrical	Minimal	Minimal	Minimal
Plumbing	None	None	None

SQUARE FOOT COSTS

CLASS	100	200	300	400	500	600	1,000	1,500	2,000	2,500
1	\$ 19.28	17.55	16.70	16.28	15.98	15.76	15.54	15.33	15.16	15.11
2	26.98	23.59	22.60	21.74	21.29	21.13	20.16	19.64	19.32	19.07
3	65.62	53.49	45.95	41.82	39.47	38.28	33.96	31.34	29.55	28.31

NOTE: Above costs include sod roof covering.

ADD For corrugated metals, light composition or wood shingles;

Class 1: \$ 3.06 per square foot of floor area Class 2: 3.67 per square foot of floor area Class 3: 4.40 per square foot of floor area

COLD STORAGE WALK-IN BOXES

TOTAL COST

TYPE	50 sq ft	100'	150'	200'	300'	400'	500'
COOL BOX	14,945	21,285	26,041	30,230	37,363	43,137	48,345
FREEZE BOX	17,051	23,957	29,069	38,438	45,571	51,345	56,553

Wall deduction per linear foot of wall: \$ 119

NOTE: Above costs represent prefabricated metal clad units, including refrigeration equipment. Deduct 10 percent for wood exterior and interior. Add 6 percent for each foot of height over 7.5 foot base height. Where building walls form exterior wall of box, use above wall deduction. For homemade boxes using farm labor for construction, deduct 30 percent.

POTATO STORAGE

TYPE I

Costs represent low quality construction, partly below grade, performed by unskilled farm labor with minimal quality materials. These are designed for relatively short storage periods. They are commonly called "potato cellars."

COMPONENT	LOW QUALITY
Foundation	None
Floor	Dirt
Frame	Wood post and beams
Walls	Minimal walls and supports used in this type of potato storage usually earthen side walls
Roof Frame	Open wood system for the use of corrugated metals, or, wood rafters, joists, and sheathing
Roof Cover	Corrugated metals or composition, roll type
Interior Components	None
Insulation	Minimal, usually vapor barrier, wire netting with straw on nailing strips or equivalent
Electrical	Minimal, service entrance and two light fixtures

LOW QUALITY SQUARE FOOT COSTS

4,000	5,000	7,000	10,000	15,000	20,000
\$ 13.46	13.04	12.36	11.92	10.99	10.12

POTATO STORAGE WAREHOUSE

TYPE II

QUONSET BUILDING: low quality prefabricated galvanized steel building with doors in end walls only, erected on concrete footings without floors, lights or plumbing. TYPE II buildings may have other uses.

SQUARE FOOT COSTS

	WIDIH						
LENGTH	30'	40'	60'	70'			
30'	17.93	-	-	-			
36'	17.09	-	-	-			
48'	15.93	14.61	-	-			
60'	15.09	13.73	13.09	-			
72'	14.45	13.13	12.56	12.04			
84'	13.93	12.68	12.00	11.64			

WIDTI

	WIDTH					
LENGTH	30'	40'	60'	70'		
96'	13.41	12.24	11.64	11.20		
108'	13.01	11.92	11.24	10.92		
120'	12.68	11.60	10.96	10.56		
160'	11.84	10.80	10.16	9.84		
200'	-	10.16	9.60	9.36		
240'	-	9.72	9.24	9.00		

OPTIONS:

Electrical		
	Minimal Service, add per square foot of floor area:	\$ 0.21
Plumbing	Minimal Service, add per square foot of floor area:	0.16
Insulation		
	If 2" thick foamglass is sprayed on walls and ceiling (or equivalent), add per square foot of insulated area:	4.38
Interior Co	onstruction	
	If potato storage area has bins and interior partitions, add per square foot of floor area:	1.71
Concrete	(or concrete flatwork)	
	Add per square foot of concreted area:	4.07

POTATO STORAGE WAREHOUSE

TYPE III

Costs represent construction at grade level using average or good quality materials with proper supervision and skilled labor. Base wall height ordinarily equals 14 feet. Most common building size equals 50 feet by 100 feet (5,000 square feet). The maximum potato storage period depends on the magnitude of temperature and humidity control equipment; however, costs do not include environmental control. Refer to Page 24 for additional environmental control costs. TYPE III buildings may have other uses.

COMPONENT	AVERAGE QUALITY	GOOD QUALITY
Foundation	Continuous concrete	Continuous concrete
Floor	Dirt	Dirt
Frame	Heavy timber post and beam. Basic height	Steel frame. Basic height 14 feet.
Exterior Wall	14 feet. Wood siding painted, 1 or 2 large end doors, one walk-in door.	Aluminum or steel, corrugated metal cover, unpainted. 2 large end doors. 1 or 2 walk-in doors.
Interior Construction	See options	See options
Ceiling	Open	Open
Plumbing	Entry service, 2 hose bibs	Entry service, 2 hose bibs
Electrical	Entry service, 3 outlets	Entry service, 3 outlets
Insulation	2 inch thick cellulose sprayed walls and ceiling or equivalent	2 inch thick cellulose sprayed walls and ceiling or equivalent
Roof Frame Roof Cover	Wood rafters, joists, sheathing Asphalt or wood shingle	Open steel and frame for corrugated metals Galvanized metal

SQUARE FOOT COSTS

	5,000	7,000	10,000	15,000	20,000	25,000	30,000	40,000
AVG	\$ 23.72	22.60	21.49	19.81	18.45	17.81	17.17	16.37
GOOD	31.37	29.68	27.51	24.84	22.96	21.77	20.89	19.95

OPTIONS:

Interior Construction

If potato storage area has bins and interior partitions,

add for average quality per square foot: \$ 4.68
add for good quality per square foot: 9.12

Exterior Construction

Painted metal exterior walls, add per square foot: \$ 0.67 Concrete or concrete flatwork per square foot: 4.07

NOTE: Above costs for potato storage warehouse assume <u>skilled labor and include contractor fees</u>. For construction performed by ranch or farm labor without contractor supervision, deduct 15 percent to 25 percent depending on the quality of the finished building. See the following page for other additional features.

POTATO STORAGE WAREHOUSE OPTIONS

TEMPERATURE AND HUMIDITY CONTROL

Air humidity control only, including fan room, louver system, humidifiers, perforated air pipe, and control panel.

SQUARE FOOT COSTS

ĺ	5	,000	7,000	10,000	15,000	20,000	25,000	30,000	40,000
ĺ	\$	3.54	3.43	3.29	3.15	3.03	2.95	2.89	2.78

AIR CONDITIONING

Includes complete refrigeration unit and controls in addition to the air and humidity system listed above.

SQUARE FOOT COSTS

	5,000	7,000	10,000	15,000	20,000	25,000	30,000	40,000
(\$ 7.71	7.46	7.16	6.85	6.61	6.42	6.30	6.05

STEEL BUILDINGS - FARM & RANCH



METAL HORSE BARN



METAL SHOP- SLANT WALL



QUONSET BUILDING

QUONSET BUILDINGS

Costs per square foot of floor area represent <u>Average Quality</u> prefabricated galvanized steel buildings with doors in end walls only and minimum additional features, erected on concrete footings without floors, lights, or heat. Adjust low quality buildings down 30 percent and good quality buildings up 25 percent based on the quality of the finished building and extra additives. Base height equals 20 feet at the center of the arch. Add or deduct 5 percent for each foot of deviation from base.

SQUARE FOOT COSTS

_	WIDTH					
LENGTH	30'	40'	60'	70'		
30'	25.61	-	-	-		
36'	24.41	-	-	-		
48'	22.75	20.87	-	-		
60'	21.55	19.61	18.69	-		
72'	20.64	18.75	17.95	17.21		
84'	19.89	18.12	17.15	16.64		

	WIDTH					
LENGTH	30'	40'	60'	70'		
96'	19.15	17.49	16.64	16.01		
108'	18.58	17.04	16.06	15.61		
120'	18.12	16.58	15.66	15.09		
160'	16.92	15.43	14.52	14.06		
200'	-	14.52	13.72	13.38		
240'	-	13.89	13.21	12.86		

PRE-ENGINEERED STEEL BUILDINGS

Costs per square foot of floor area represent <u>Average Quality</u> prefabricated galvanized steel buildings, with minimum doors, windows, and additional features erected on concrete footings without floors, lights, or heat. Multipliers appear below for other types of skin coverings. Adjust low quality buildings down 25 percent and good quality buildings upwards 25 percent based on the quality of the finished building and extra additives.

AVERAGE QUALITY

	EAVE	LENGTH TO WIDTH RATIO					
WIDTH	HEIGHT	1.0	1.5	2.0	3.0	4.0	5.0
20'	10'	\$ 22.75	21.53	20.71	19.60	18.81	18.25
30'	12'	19.52	18.63	18.17	17.17	16.64	16.25
40'	14'	19.82	18.57	17.78	16.67	15.90	15.36
50'	14'	17.56	16.90	16.46	15.85	15.42	15.11
60'	14'	16.02	15.49	15.14	14.68	14.37	14.22
80'	16'	16.38	15.80	15.41	14.88	14.35	14.11
100'	16'	16.02	15.36	14.88	14.27	13.89	13.53
140'	16'	14.22	13.79	13.41	13.02	12.67	12.48
160'	18'	14.07	13.66	13.37	12.94	12.66	12.44
200'	18'	13.23	12.89	12.66	12.35	12.10	11.93

See following pages for additional features.

PRE-ENGINEERED STEEL BUILDINGS ADDITIONAL FEATURES

HEIGHT: add or deduct 2 percent for each foot of deviation from base.

ALUMINUM: multiply base costs by 1.05.


ENAMELED STEEL: multiply base costs by 1.05.

SLANT WALL BUILDINGS: deduct 5 percent to 15 percent.

Costs based on square foot of floor area, unless otherwise noted.

COSTS PER SQUARE FOOT	LOW	AVG	GOOD		
FLOOR:					
Asphalt:	\$ 2.04	\$ 2.58	\$ 3.27		
Concrete:	3.36	4.07	4.94		
LIGHTING:	0.24	0.67	1.31		
INSULATION: (per square foot of insulated wall area) Wall: \$ 0.72 \$ 0.87 \$ 1.00					
Roof:	0.93	1.42	2.15		
PLUMBING:	0.21	0.61	1.20		
HEATING: (suspended space heaters):	0.99	1.34	1.82		

PREFABRICATED METAL HORSE STABLES



AVERAGE QUALITY
SINGLE STALL

AVERAGE QUALITY

QUADRUPLE STALL

AVERAGE QUALITY

DOUBLE STALL

WITH PATIO ROOF
OR OVERHANG

AVERAGE QUALITY

QUADRUPLE STALL

WITH PATIO ROOF
OR OVERHANG

BASIC FARM BUILDINGS

PREFABRICATED METAL HORSE STABLES

COMPONENT	CLASS 1 LOW QUALITY	CLASS 2 AVERAGE QUALITY	CLASS 3 GOOD QUALITY
Foundation	Light perimeter concrete foundation	Average perimeter concrete foundation	Good perimeter concrete foundation
Floor	Dirt	Dirt	Dirt
Wall Structure	Prefabricated light metal frame	Prefabricated average weight metal frame	Prefabricated heavy duty metal frame
Exterior Wall Cover	Metal cover light weight	Metal cover average weight	Metal cover heavy duty
Roof Construction	Light open steel system for metal	Average open steel system for metal	Heavy duty open steel system for metal
Roof Cover	Low pitch light metal cover	Low pitch average metal cover	Low pitch heavy duty metal cover

SQUARE FOOT COSTS

	ONE STABLE	TWO STABLES	FOUR STABLES
CLASS	144 SF	288 SF	576 SF
1	\$ 18.77	\$ 17.20	\$ 15.75
2	25.01	22.98	21.11
3	33.36	30.73	28.32

ADD per square foot of patio roof or overhang:

LOW	AVG	GOOD	
\$ 4.30	\$ 6.04	\$ 8	.48

ADD Concrete or concrete flatwork per square foot: \$ 4.07

NOTE: Above costs are based on <u>professional construction labor supervised by a contractor or his job foreman</u>. For farm labor with no professional supervision, costs should be adjusted downward by 25 percent relative to the quality of the finished product.

2017-2018 RURAL BUILDING COST MANUAL

Section 2

DAIRY BARNS






PHOTOS COURTESY OF CHURCHILL COUNTY ASSESSOR


LOW QUALITY




GOOD QUALITY








VERY GOOD QUALITY



DAIRY BARNS


Stanchion Barn




Typical Walk-Through

Component Parts of This Dairy

- A. Milking Barn B. Milk, Wash, and Equipment Rooms



Cross Section Modern Herrington-Type Dairy Barn



Section 2

MILKING PARLORS

SITE PREPARATION	Basically level terrain, no excavation, minimum fill.
FOUNDATION	Reinforced concrete for one story height. Foundation and footings formed and poured monolithically with floor slab.
FLOORS	Concrete well formed gutters, elevated slab.
CEILING	Open unfinished, paint only, bottom of roof.
INTERIOR	Type found in dairies and milking parlors, smooth plaster or epoxy paints. Minimum cow stanchions and stalls conforming to the quality of the building. No equipment nor machinery is included.
PLUMBING	Basic plumbing required for building, usual floor drains and hose bibs. Does not include milk piping, pumps or storage.
HEATING - COOLING	Minimum, space heaters and evaporative coolers.
ELECTRICAL	Basic electrical service required for dairies. Does not include machinery or equipment.
LIGHTING EXTERIOR WALLS	8" concrete block, bearing walls or reinforced concrete 36 inch high with 2" x 6" stud framing – 16" on center above.
ROOF STRUCTURE AND COVER	Wood joists, wood or composition deck. Asphalt shingles to 290 pounds.
COST RANGE RATING	Based on cost per square foot of floor area.

SQUARE FOOT COST

QUALITY

LOW	AVERAGE	GOOD	VERY GOOD
\$ 53.32	\$ 66.39	\$ 83.65	\$ 106.46

NOTE: Above costs are based on <u>professional construction labor supervised by a contractor or his job foreman.</u>

For farm labor with no professional supervision, costs should be adjusted downward by 25 percent relative to the quality of the finished product.

MILKING PARLORS

ADDITIONAL FEATURES

COST RANGE RATING Based on cost per square foot of floor area unless otherwise noted.*

QUALITY

FEATURE	LOW	AVERAGE	GOOD	VERY GOOD
CEILING				
(Gypsum board - taped and painted):	\$ 2.06	2.28	2.52	2.79
INSULATION				
Walls:	\$ 0.71	0.86	1.05	1.28
Roof:	0.92	1.41	2.13	3.22

WALL ORNAMENTATION				
(*apply only to ornamented area):				
	LOW	AVERAGE	GOOD	VERY GOOD
CERAMIC TILE				
(*cost based on square foot of area covered)	:			
	12.83	15.76	18.70	21.63
ROOF COVER]			
(Wood shingle):	5.02	6.24	7.77	9.68
AUTOMATIC GATES	1			
(*based on cost per stall):	\$ 1,199	\$ 1,277	\$ 1,354	\$ 1,432
AUTOMATIC FEED EQUIPMENT			FOR AL	JGER ADD: \$ 860
(*based on cost per stall):	\$ 860	941	1,023	1,104

FEED STORAGE BINS (see pages 3 & 4, section 6)

NOTE: Above costs are based on <u>professional construction labor supervised by a contractor or his job foreman</u>. For farm labor with no professional supervision, costs should be adjusted downward by 25 percent relative to the quality of the finished product.

MILK STORAGE, WASH, AND EQUIPMENT ROOMS

SITE PREPARATION	Basically level terrain, no excavation, minimum fill.
FOUNDATION	Reinforced concrete for one story height. Foundation and footings formed and poured monolithically with floor slab.
FLOORS	Concrete at grade level, may include some gutters and drains.
CEILING	Gypsum board, taped and painted.
INTERIOR	Type found in dairies and milking parlors, smooth plaster or epoxy paints. No equipment or machinery is included.
PLUMBING	Basic plumbing required for building, wash basins, water closet, lavatory. Does not include milk piping, pumps or storage.
HEATING - COOLING	Minimum, space heaters and evaporative coolers.
ELECTRICAL LIGHTING	Basic electrical lighting service required for building.
EXTERIOR WALLS	8" concrete block, bearing walls for good and very good quality, plywood, boards, or wood siding on wood frame, interior sheathing finished for low and average quality.
ROOF STRUCTURE AND COVER	Wood joists and sheathing, asphalt shingle cover.
COST RANGE RATING	Based on cost per square foot of floor area.

SQUARE FOOT COSTS QUALITY

LOW	AVERAGE	GOOD	VERY GOOD
\$ 26.49	\$ 36.61	\$ 62.20	\$ 81.81

NOTE: Above costs are based on <u>professional construction labor supervised by a contractor or his job foreman</u>. For farm labor with no professional supervision, costs should be adjusted downward by 25 percent relative to the quality of the finished product.

MILKING STORAGE, WASH AND EQUIPMENT ROOMS

ADDITIONAL FEATURES

COST RANGE RATING Based on cost per square foot of floor area.

QUALITY

FI	EATURE	LOW	AVERAGE	GOOD	VERY GOOD
INSULATION					
	Walls:	0.71	0.86	1.05	1.28
	Roof:	0.92	1.41	2.13	3.22
WALL ORNAM (*apply only to orr CERAMIC TILE	namented area):				
	- uare foot of area cover	ed):			
		12.83	15.76	18.70	21.63
ROOF COVER					
(Wood shingle):		5.02	6.24	7.77	9.68

NOTE: Above costs are based on <u>professional construction labor supervised by a contractor or his job foreman.</u> For farm labor with no professional supervision, costs should be adjusted downward by 25 percent relative to the quality of the finished product.



FEEDER FENCE w HEADLOCK

WASH PEN AND HOLDING AREA

FLOOR OR RAMP	Sloping concrete slab rough finish 6" thick.
WALLS	Concrete block 8" - height 5'.
FENCING	Welded iron pipe, post 10' on center set in concrete, pipe top rail with 3 cable strands, or, no pipe top rail with 5 cable strands, or, iron rods. Cable size 5/8" or ¾".
GATES	Metal gates (2 usually) 12 linear feet each, 5 rail.
SPRINKLER	Hooded rainbird type or equivalent including piping and pump.
COST RANGE RATING	Based on cost per square foot of floor area.

QUALITY

LOW	AVERAGE	GOOD	VERY GOOD
\$ 13.83	\$ 15.09	\$ 16.52	\$ 18.11

ROOF COVERING: Wood or pipe post and beam, steel trusses, light metal roof cover;

QUALITY

LOW	AVERAGE	GOOD	VERY GOOD
\$ 6.96	\$ 8.96	\$ 11.51	\$ 14.82

METAL RAIL FENCE WELDED IRON RAILS

Iron pipe post 2-1/2" to 4" in diameter - 7' to 10' on center in concrete:

\$ 16.48 per linear foot.

CABLE FENCE

Iron pipe post 2-1/2" to 4" in diameter - 7' to 10' on center in concrete -

iron pipe top rail;

3-Cable: \$ 13.26 per linear foot. 4-Cable: \$ 14.87 per linear foot.

METAL GATES

54" to 64" high - welded iron rails or pipe with bracing:

19.43 per linear foot of gate width.

NOTE: Above costs are based on <u>professional construction labor supervised by a contractor or his job foreman.</u>
For farm labor with no professional supervision, costs should be adjusted downward by 25 percent relative to the quality of the finished product.

DAIRY EQUIPMENT STAINLESS STEEL REFRIGERATED HOLDING TANKS

SIZE	TANK	COMPLETE
GALLONS	ONLY	SYSTEM
500	\$ 8,297	\$ 15,705
1,000	15,596	22,439
1,250	18,246	25,762
1,500	20,396	27,993
2,000	25,197	34,141
2,500	28,999	41,487
3,000	31,802	48,834
4,000	38,406	60,583
5,000	43,013	71,801

VACUUM PUMP SYSTEMS

8-20 STALLS WITH 3 PHASE ELECTRIC MOTORS
PER COW STALL: \$ 446

REFRIGERATION COMPRESSORS

HORSE POWER	COST
3.0	\$ 5,588
4.0	8,166
5.0	10,743
7.5	13,321
10.0	15,899
15.0	18,476

FEED FENCING w HEADLOCKS

TYPE	COST
STEEL	\$ 26.55 per LF
LOCKABLE STEEL	39.85 per LF
SELF-LOCKING STEEL	78.23 EACH

NOTE: See following page for listing of additional equipment.

DAIRY EQUIPMENT

PLATE COOLERS

NUMBER OF STALLS

6	8	12	20	24
\$ 4,301	6,389	8,478	10,566	12,654

HERRINGBONE STALLS

SIZE	STALLS	COST
DOUBLE 3	6	\$ 10,739
DOUBLE 4	8	12,821
DOUBLE 6	12	19,231
DOUBLE 10	20	32,051
DOUBLE 12	24	33,966

NOTE: Above costs include manually operated gates. Larger or other sizes, use a combination of above.

MILK TRANSFER LINES

ТҮРЕ	SIZE	COST PER LF
STAINLESS STEEL	18 GAUGE - 1.5"	\$ 7.46
STAINLESS STEEL	18 GAUGE - 2.0"	9.47
STAINLESS STEEL	16 GAUGE - 2.0"	12.33
STAINLESS STEEL	16 GAUGE - 2.5"	17.12
STAINLESS STEEL	16 GAUGE - 3.0"	20.69
GLASS PIPE	1.5"	57.66
GLASS PIPE	2.0"	71.43

NOTE: Flushing systems require twice the amount of pipe.

Electric pulsator or hydropulsator;

Manual on & off: \$ 505 to \$ 808 Automatic off, add: \$ 843 to \$ 2,525

2017-2018 RURAL BUILDING COST MANUAL

Section 3

BUNK HOUSES


BUNK HOUSES




CLASS I LOW QUALITY



CLASS 2
AVERAGE QUALITY





CLASS 4
VERY GOOD QUALITY

BUNK HOUSES

	CLASS 1	CLASS 2	CLASS 3	CLASS 4
COMPONENT	LOW QUALITY	AVERAGE QUALITY	GOOD QUALITY	VERY GOOD QUALITY
Foundation	Thickened slab around perimeter	Thickened slab around perimeter Thickened slab around perimeter		Spread footing around perimeter and thickened slab at partitions
Floor	4" concrete slab	4" concrete slab	4" concrete slab	4" concrete slab
Walls	48" on center 48" on center cer		2"x4" studs at 24" on center, 2"x4" stud partitions at 24" on center	Masonry exterior walls wood frame interior partitions and ceiling
Exterior Cover	Cheap grade redwood or Douglas fir vertical or horizontal	Average grade of redwood, Douglas fir, B and B or horizontal board	Average or better grade of redwood B and B or horizontal siding or stucco finish	Natural blocks
Interior Finish	None	Gypsum board or plywood partitions painted	Gypsum board or plywood partitions painted	Sheet rock finished
Roof Framing	line ceiling		Rafters, collar beams and ceiling joists or good trusses	Rafters, collar beams and ceiling joists or good trusses
Roofing	Composition or used metal sheeting	Composition or metal sheeting	Aluminum or corrugated iron or light wood shingles	Good grade composition shingles or wood shingles
Doors	Two or three cheap doors	Three or four average doors	One average door each room	One good door each room
Windows	Few and small	One window each room	One steel or aluminum window in each room	One steel sash or aluminum window in each room
Electrical	Minimum outlets	Minimum outlets	Average or better outlets	Average or better outlets adequate amount
Heating & Cooling	None	None	None	None

BUNK HOUSES

SQUARE FEET

CLASS	400	600	800	1,000	1,200	1,500	2,000	2,500	3,000
1	\$ 23.48	22.19	21.54	20.83	20.57	19.95	19.50	19.11	18.94
2	31.39	29.71	28.96	28.03	27.68	26.90	26.29	25.83	25.63
3	42.52	40.39	39.37	38.23	37.80	36.77	36.02	35.43	35.12
4	76.25	70.66	68.08	64.81	63.79	61.00	59.02	57.32	56.57

1. Utility hook-up costs included.

2. Interior plumbing not included Add for Class 1: \$ 807 per fixture

Class 2: 1,233 per fixture
Class 3: 1,883 per fixture
Class 4: 2,915 per fixture

3. Domestic well or septic system not included. Refer to Section 4 for costs

4. Floor covering not included. Add asphalt title or linoleum: \$ 5.18 per sq ft

Add installed carpet: 5.25 per sq ft

5. Cooling systems not included. Add window units: \$ - per sq ft

Add for evaporative coolers, roof or wall units only: 2.73 per sq ft

6. Heating systems not included. Add floor or wall furnace: 1.57 per sq ft

7. Insulation not included. Add for Roof: 1.42 per sq ft

Walls: 0.87 per sq ft

NOTE: Above costs are based on <u>professional construction labor supervised by a contractor or his job foreman.</u>
For farm labor with no professional supervision, costs should be adjusted downward by 25 percent relative to the quality of the finished product.

2017-2018 RURAL BUILDING COST MANUAL

Section 4

UTILITIES

UTILITIES


DOMESTIC WATER SYSTEMS - SEPTIC SYSTEMS - MOBILE HOME HOOKUPS

NOTE: The costs offered in this section represent general or average costs. Actual costs in specific geographic areas may vary substantially thereby requiring each assessor to substitute locally relevant cost data.

<u>Residence and bunkhouse</u> costs already include utility hookups. Mobile home hookup costs appear on Page 3 of this section.

PRESSURE TANK SIZES

42 gallons	16 inch diameter	Χ	48 height	50 inch circumference
3		٨	J	
82 gallons	20 inch diameter	Χ	60 height	63 inch circumference
120 gallons	24 inch diameter	Х	60 height	75 inch circumference
220 gallons	30 inch diameter	Х	72 height	94 inch circumference
315 gallons	36 inch diameter	Х	72 height	113 inch circumferenc
525 gallons	36 inch diameter	Х	120 height	113 inch circumferenc



UTILITIES DOMESTIC WATER SYSTEMS

JET PUMPS

Includes a completely installed shallow well system package. <u>Does not include</u> well drilling. **Bold** cells show typical configurations.

PUMP MOTOR (HP)

TANK						
(GAL)	1/3	1/2	3/4	1	11/2	2
40	1,212	1,423	1,689	1,767	2,044	2,433
80	1,276	1,487	1,754	1,831	2,109	2,497
120	1,401	1,611	1,878	1,956	2,233	2,622
220	1,845	2,055	2,322	2,400	2,677	3,066
315	2,111	2,322	2,588	2,666	2,943	3,332
525	2,505	2,716	2,982	3,060	3,337	3,726

EXAMPLE: 3/4 HP & 80 GAL TANK \$ 1,754

6" WELL AT 60' DEPTH 2,280

.

TOTAL COST \$ 4,034

SUBMERSIBLE PUMPS

Includes pump, piping at well, pressure tank, and pad. <u>Does not include</u> well drilling. **Bold** cells show typical configurations.

PUMP MOTOR (HP)

Т	Δ	N	K
1.	Δ	LN	\mathbf{r}

(GAL)	1/3	1/2	3/4	1	11/2	2	3	5
40	1,171	1,434	1,684	1,976	2,420	2,983	3,166	5,086
80	1,235	1,499	1,748	2,040	2,484	3,047	3,227	5,147
120	1,360	1,623	1,873	2,165	2,609	3,171	3,332	5,253
220	1,804	2,067	2,317	2,609	3,053	3,615	3,754	5,674
315	2,070	2,333	2,583	2,875	3,319	3,882	3,948	5,869
525	2,464	2,727	2,977	3,269	3,713	4,276	4,392	6,313

EXAMPLE: 1 HP PUMP & 120 GAL TANK \$ 2,165

8" WELL AT 100' DEPTH. 5,700

TOTAL COST \$ 7,865

WELL DRILLING

Drilling & casing costs per foot of well depth 4" - 6" WELL: \$ 38 per foot (includes gravel and concrete packing) 8" - 10" WELL: 57 per foot

NOTE: Above costs are based on <u>professional construction labor supervised by a contractor or his job foreman.</u>
For farm labor with no professional supervision, costs should be adjusted downward by 25 percent relative to the quality of the finished product.

UTILITIES

SEPTIC TANKS

The first table contains average septic tank costs gathered from a statewide market survey of excavating and construction companies conducted in 1991, adjusted for time. The second table contains costs derived from the current Marshall Swift Commercial Manual without any adjustment for farm labor. Assessors should apply their knowledge of local market conditions to select an appropriate value.

Segregated by common sizes, these costs represent septic tanks installed and connected in normal soil with leach fields and lines, <u>but do not include hookup costs</u>, which are included with residences or <u>bunkhouses</u>. For mobile homes, add the sewer hookup costs listed below.

1991 MARKET SURVEY

CAPACITY (GAL)

AREA	1,000	1,250	1,500
CARSON CITY	\$ 3,423	3,768	4,130
RENO	3,952	4,241	4,950
ELKO	3,537	4,014	4,485
PAHRUMP	2,592	2,836	3,537
LAS VEGAS	2,416	2,890	3,483

MARSHALL SWIFT JUNE 2015

CAPACITY (GAL)

QUALITY		1,000	1,250	1,500
LOW	\$	1,873	2,380	2,743
AVERAGE		2,775	3,395	3,959
GOOD		3,842	4,569	5,378

MOBILE HOME HOOKUPS

TYPE		LOW	AVG	GOOD
Water	\$	737	989	1,383
Electric		1,103	1589	2,298
Sewer		829	1212	1,543
Gas		349	526	846

WATER hookups include trenching, pipe, and labor from unit to city main or domestic well system.

ELECTRIC hookups include pole, box, overhead wiring, and conduit for a 100 ampere system.

SEWER hookups include trenching, pipe, and labor to a city sewer main or septic system.

GAS hookups include trenching, pipe, and labor from unit to a gas main or a tank and regulator.

NOTE: Mobile home hookup costs do not include connector, service, or user fees.

Hookup costs do include combined piping for 40 linear feet of water and sewer lines.

For either water or sewer piping costs exceeding base, ADD per linear foot: \$6.77 to \$11.22

2017-2018 RURAL BUILDING COST MANUAL

Section 5


CORRALS AND FENCES




RAILROAD TIE POSTS 10' OC POLE RAIL FENCE AVERAGE QUALITY LESS 15 %



RAILROAD TIE POSTS
POLE RAIL FENCE
WITH FEED TROUGH
AVERAGE QUALITY



RAILROAD TIE POSTS
CABLE FENCE
WITH FEED TROUGH
AVERAGE QUALITY



RAILROAD TIE POSTS 6' OC 2" X 8" FENCE RAILS AVERAGE QUALITY PLUS 15%



RAILROAD TIE POSTS 8' OC 2" X 8" FENCE RAILS WITH POLES GOOD QUALITY



RAILROAD TIE POSTS
CABLE FENCE
WITH FEED TROUGH
AVERAGE QUALITY

CORRAL FENCING COST PER LINEAR FOOT

TYPE	LOW	FAIR	FAIR AVG	
WOOD	\$ 8.90	\$ 10.71	\$ 12.93	\$ 15.56
Examples	4-4"	4-6"	5-6" 7-6	
of Rails	3-6"	3-8"	4-10"	6-8"
	2-10"	2-12"	3-12"	4-12"
	2 or 3 poles	4 or 5 poles	6 or 7 poles	7 or 8 poles

Base costs include railroad tie posts eight feet on center with two inch thick rails. Reduce fair – good quality by one class for lighter wood posts or one inch thick rails; reduce low quality by 20 percent. Adjust base cost plus or minus 7.5 percent for each foot of deviation from base of eight feet on center. Less than eight feet, increase costs, more than eight feet, reduce costs. For solid wood fence of two inch thick rails add 35 percent to good quality. Do not adjust base cost overall more or less than 50 percent.

TYPE	LOW	FAIR	AVG	GOOD
WIRE	\$ 3.21	\$ 3.85	\$ 4.50	\$ 5.14
Examples:	2 or 3 strands barbed or hog/cattle fence	3 or 4 strands barbed or light grade woven or welded wire	5 or 6 strands barbed or horse fence (medium welded wire)	7 or 8 strands barbed or bull panels (heavy welded wire)

Base costs include railroad tie posts eight feet on center. Adjusted cost plus or minus 7.5 percent for each foot of deviation from base. Reduce one class for lighter wood posts; reduce two classes for metal "T" posts. Reduce low quality by 30 percent for light wood posts or 50 percent for metal "T" posts. Do not adjust base cost overall more or less than 50 percent.

PIPE AND CABLE FENCES

ТҮРЕ	LOW	FAIR	AVG
4" PIPE, CABLE RAILS	\$ 12.71	13.12	13.52
4" PIPE, 2" PIPE RAILS	16.21	16.72	17.24

WOODEN FEED TROUGHS

TYPE	LOW	FAIR	AVG	GOOD
W/O FENCE	\$ 6.93	\$ 9.16	11.74	16.55
WITH FENCE	\$ 9.75	12.65	15.47	20.15

For metal troughs, add 200 percent. For concrete troughs, add 250 percent.

CONCRETE

In-place cost for flatwork per square foot: \$ 4.07 to \$ 4.94 Cost per square foot of wall area: \$ 19.93


METAL FENCING AND GATES




5' CHAIN LINK FENCE NO TOP RAIL



COMMERCIALLY MANUFACTURED GATE GOOD QUALITY



EXPANDED TUBE STEEL GATE



IRON PIPE CORRAL
AND HOLDING PEN

CHAIN LINK FENCING

Average cost per linear foot, including complete installation on two inch round or "H" posts set in concrete, 8 to 12 feet on center.

	HEIGHT				
ТҮРЕ	4'	6'	8'	10'	12'
2" INCH MESH AVERAGE QUALITY	\$ 8.73	12.59	16.58	20.47	24.23
ADD FOR RAILS	1.94	1.94	2.10	2.10	2.10
ADD FOR PRIVACY SLATS	5.90	8.99	12.09	15.49	18.57
ADD FOR 3 STRAND BARBED WIRE	2.52	2.52	2.84	2.84	2.84

Add 5 percent to 15 percent for aluminum or vinyl covered wire.

PORTABLE HORSE CORRALS & GATES

ТҮРЕ	L	OW	F	FAIR	1	AVG	G	OOD
METAL PIPE OR	¢	7.55	¢	12.02	¢	16.05	¢	23.29
PORTABLE PANELS	Þ	7.33	Ф	12.02	Φ	10.05	\$	23.29

Gates may be included in linear footage of fencing, commensurate to quality class, height, etc.


PLASTIC FENCING

ТҮРЕ	C	COST
POLYMER GRID , 5', 2" * 6" TOP RAIL	\$	14.03
VINYL FENCE, 5" * 5" POSTS, 3 - 2" * 6" RAILS		17.70

For other types of plastic fence, see the Marshall & Swift Commercial Manual, Section 66 Page 5


NOTE: Above costs are based on <u>professional construction labor supervised by a contractor or his job foreman</u>. For farm labor with no professional supervision, costs should be adjusted downward by 25 percent relative to the quality of the finished product.

CORRAL LOADING CHUTES



LIGHT SPACED CHUTE

HEAVY SPACED CHUTE





HEAVY SOLID CHUTE

CORRAL LOADING CHUTE COST PER LINEAR FOOT INCLUDING BOTH SIDES

SPACED	LIGHT CHUTE	\$ 66.10 per lf
	HEAVY CHUTE (INCLUDES PLATFORM)	70.50
SOLID	LIGHT CHUTE	74.91
	HEAVY CHUTE (INCLUDES PLATFORM)	79.32

CONCRETE DIPPING VAT

USUALLY COMPOSED OF:

Six inch electric welded fabric, reinforced concrete wade in dipping vat.

Three foot six inches wide by 30 feet long and four feet deep with two inch supply and drain lines included.


Pump and valve not included.

COMPLETE IN PLACE COST \$ 4,740



CALF TABLE

WINDMILLS & CATTLE SQUEEZES



COMMERCIALLY MANUFACTURED HEAVY DUTY CATTLEGUARDS

7.	5' x 8'	7.5' x 10'	7.5' x 12'	7.5' x 15'
\$	2,420	\$ 3,269	\$ 4,118	\$ 4,967

CATTLE SQUEEZE

STATIONARY MODEL, LIGHT	\$ 1,850
STATIONARY MODEL, HEAVY	3,843
HEAVY DUTY, HYDRAULIC	14,602
CALF TABLE	1,238



HEAVY STATIONARY SQUEEZE

WINDMILLS AND STEEL TOWERS

]	FAN	TO	OWER	INSTALLATION	TOTAL COST
6'	\$ 2,007	21'	\$ 2,124	\$ 2,140	\$ 6,272
6'	2,007	27'	2,753	2,066	6,827
6'	2,007	33'	3,411	2,297	7,715
8'	2,574	21'	2,124	1,962	6,660
8'	2,574	27'	2,753	1,666	6,993
8'	2,574	33'	3,411	1,896	7,881
10'	4,457	27'	2,753	2,336	9,546
10'	4,457	33'	3,411	2,344	10,212
12'	7,060	27'	2,753	3,285	13,098
12'	7,060	33'	3,411	3,516	13,986
14'	11,161	27'	2,753	4,512	18,426
14'	11,161	33'	3,411	5,853	20,424
16'	15,149	33'	3,411	6,526	25,086

Includes complete steel wheel, tower and installation excluding well.

CATTLE AND HORSE WATERING TANKS ROUND BOTTOMLESS STOCK TANKS

25.5 INCH DEEP, GALVANIZED CORRUGATED

PER FOOT OF DIAMETER - 22 GAUGE METAL \$ 32.30

12 GAUGE METAL \$ 53.26

ADD: 10 GAUGE METAL

25%

PER SQUARE FOOT OF CONCRETE SLAB

4.07

COMMERCIALLY MANUFACTURED METAL WATER TANKS

25.5" TO 27" DEEP, GALVANIZED WITH BOTTOM

PER FOOT OF DIAMETER - 22 GAUGE METAL \$ 40.38

12 GAUGE METAL \$ 68.80

ADD: 10 GAUGE METAL 25%
PER SQUARE FOOT OF CONCRETE BASE \$ 4.07

COMMERCIALLY MANUFACTURED AUTOMATIC WATERERS WITH HEATERS

LEN	WDTH	HGHT	GAL	HEAD	COST
20	18	25	3	30 50	\$ 433
30	24	25	9	80 120	575
32	28	25	13	100 200	684
42	28	25	20	200 300	775
66	28	25	35	300 400	875
84	24	16	40	350 450	911
90	28	25	50	400 550	985
90	36	25	120	500 700	1,075
120	28	25	120	500 700	1,200

COMMERCIALLY MANUFACTURED METAL WATER TROUGHS

(GALVANIZED TANK)

GALLONS					
175	300	500	900		
\$ 172	\$ 233	\$ 311	\$ 472		

ALL OTHER WATER TROUGHS

1 cubic foot = 7.5 gallons

VOLUME	COST /	(GAL	Cu	Ft
LESS THAN 100 GALLONS		\$	3.00	\$	22.48
100 TO 175 GALLONS			2.74		20.53
176 TO 300 GALLONS			2.48		18.58
301 TO 500 GALLONS			2.21		16.63
OVER 500 GALLONS			1.95	I I	14.67

COMMERCIALLY MANUFACTURED METAL FENCE PANELS

Portable or stationary, not including posts. For wooden posts (RR Ties)

	Add	\$	7.21	to	\$ 18.62	EACH	
					6'	\$	140
					8'		186
64" HEIGHT, 5 RAIL MEDIUM DUTY				10'		206	
04 HEIGHT, 5 KF	AIL IVIL	_DI	ו ו טע ועונ		12'		223
					14'		259
					16'		284
				6'	\$	223	
		8'		266			
64" HEIGHT, 5 RAIL EXTRA HE	EVVA DIILA	/	10'		293		
		~ ! !	LAVIDUI	ı	12'		332
				14'		380	

For extra heavy duty panels with solid steel sections, increase cost 100%.

16'

414

COMMERCIALLY MANUFACTURED METAL GATES w LEVER LATCH

WIDTH					
6 FOOT	8 FOOT	12 FOOT	16 FOOT		
\$ 226	\$ 268	\$ 335	\$ 416		

COMMERCIALLY MANUFACTURED PROFESSIONAL ROPING AND DOGGING CHUTE

FIRST SECTION WITH RELEASE GATE	\$ 2,625
SECOND SECTION	1,853
STRIPPING CHUTE	885

COMMERCIALLY MANUFACTURED BUCKING CHUTE

FIRST SECTION	\$ 5,092
ADDITIONAL SECTIONS, EACH	3,966

COMMERCIALLY MANUFACTURED CROWDING ALLEYS

24' x 60" INCLUDES FRAMES & HEADGATE w STAND	\$ 2,557
24' x 60" ADD-ON SECTION	1,035
ALLEY STOPS ADD	183
10' CUTOUT GATE INCLUDING FRAME AND 10' PANEL	901

CURVED CROWDING ALLEYS


180 DEGREE SWEEP, 10' GATE & 24' ADJUSTABLE ALLEY		
WITH A1 CAGE & 10' X 20' LEAD-UP	\$ 5,	,699
180 DEGREE SWEEP, 10' GATE & 24' ADJUSTABLE ALLEY	4,	,092
BLOCKING DOOR ADD		774
ADJUSTABLE ALLEY BOW		165

COMMERCIALLY MANUFACTURED FEEDER PANEL

SIZE	EACH		
6' x 64"	\$	381	
8' x 64"		469	
10' x 64"		557	
12' x 64"		646	
16' x 64"		839	

HEADGATES

SELF CATCH HEAVY DUTY	\$ 1,773
SELF CATCH LIGHT DUTY	839



180' SWEEP w CROWDING ALLEY

2017-2018 RURAL BUILDING COST MANUAL

Section 6

MISCELLANEOUS COSTS

Most of the costs in this section are based on <u>professional construction labor supervised by a contractor or his job foreman</u>. Few of these costs should be adjusted downward for farm labor with no professional supervision, as most of these items are professionally installed with contractor supervisor.



SILO: GLASS-LINED STEEL



GRAIN STORAGE BINS with CONVEYOR

FARM SILOS

Costs of concrete stave silo, complete. For other construction material, see factors listed below.

TOTAL COST

HEIGHT

DIAMETER	30'	35'	40'	45'	50'	60'	70'	80'	90'
12'	\$ 12,302	14,460	16,618	18,668	20,719	24,819	-	-	-
14'	14,352	16,726	19,100	21,420	23,740	28,488	33,128	-	-
16'	14,892	17,266	19,640	22,176	24,711	29,459	34,423	39,279	-
18'	15,971	18,614	21,258	23,956	26,654	31,941	37,229	42,409	47,696
20'	17,805	20,773	23,740	26,816	29,891	35,826	41,653	47,588	53,415
22'	20,827	24,280	27,733	31,132	34,531	41,545	48,236	55,034	62,048
24'	-	-	-	-	39,819	47,696	55,574	63,127	71,221
30'	-	-	-	-	-	64,746	75,537	86,058	96,579

No chute, deduct per vertical foot of height \$ -Flat roof, deduct per square foot of floor area \$ 5.91 No roof, deduct per square foot of floor area \$ 11.17

NOTE: For silos constructed from other materials, multiply the costs above by these factors:

Brick masonry	1.75	Glass lined steel	2.15
Reinforced concrete	1.60	Steel	1.80
Concrete block	1.20	Wood	1.10

SILO UNLOADER

EACH

	12'	14'	16'	18'	20'	22'	24'	26'	28'	30'
\$	9,766	10,251	10,899	11,438	12,194	12,733	13,381	N/A	N/A	14,136

NOTE: Above costs are based on <u>professional construction labor supervised by a contractor or his job foreman.</u>
For farm labor with no professional supervision, costs should be adjusted downward by 25 percent relative to the quality of the finished product.

STEEL GRAIN BINS

Costs are averages for utility type storage bins usually found on farms and ranches. Costs of standard bins are for tank with door and manhole, erected on buyer's slab. Height is to top of shell. Cost of ventilated floor includes floor, auger tube, and steel columns and beam supports for plenum assembly.

NOTE: To calculate capacity in bushels, multiply diameter squared x height x .63.

SI'	ZE	CAPACITY	COST W/O	COST WITH	
DIAM	HGHT	(BUSHELS)	DRY BIN	DRY BIN	SLAB FLOOR
15	7	1,257	\$ 5,162	\$ 7,548	\$ 722
15	11	1,792	6,827	9,990	788
15	15	2,329	8,159	11,877	899
15	18	2,864	9,158	13,431	1,043
18	11	2,647	7,548	11,045	966
18	15	3,422	9,324	13,653	1,005
18	18	4,198	10,601	15,429	1,043
21	11	3,693	8,381	12,099	1,332
21	15	4,753	10,601	15,429	1,376
21	18	5,813	12,876	18,648	1,432
24	11	4,949	10,212	14,874	1,676
24	15	6,344	12,432	18,204	1,754
24	18	7,739	15,540	22,644	1,832
27	11	6,409	12,099	17,649	2,165
27	15	8,182	14,985	21,534	2,264
30	15	10,278	18,093	26,307	2,498
30	18	12,473	21,312	31,191	2,631
30	22	14,668	24,753	-	2,775
30	26	16,863	27,528	-	3,025
36	15	15,297	25,641	37,185	3,691
36	18	18,473	29,082	42,402	3,913
36	22	21,648	33,855	-	4,079

	ADD:		PER SQUARE FOOT OF CONCRETE SLAB \$ 4.07
LADDERS	\$ 73	PLUS	\$ 10.40 PER LINEAR FOOT
SAFETY CAGES	20.26	TO	25.09 PER FOOT INSTALLED
AUGER AND DRIVE	433	PLUS	42.18 PER FOOT OF TANK DIAMETER
SPREADERS	844	TO	1,265 EACH
STIRRATORS	194.25	TO	299.70 PER FOOT OF TANK DIAMETER

NOTE: Above costs are based on <u>professional construction labor supervised by a contractor or his job foreman.</u>
For farm labor with no professional supervision, costs should be adjusted downward by 25 percent relative to the quality of the finished product.

FEED TANKS

Costs are averages of typical farm hoppers with roof, manhole, and ladder including necessary steel structural supports and concrete footings. Height is overall from ground level to top of tank. Capacity in tons is figured at 50 pounds per bushel.

DIAMETER	HEIGHT	CAPACITY	CAPACITY	
(FEET)	(FEET)	(BUSHELS)	(TONS)	COST
6	10'	120	3.0	\$ 1,931
6'	16'	240	6.0	2,753
6'	21'	360	9.0	3,108
6'	25'	480	12.0	3,524
6'	28'	600	15.0	3,857
7'	11'	157	4.0	2,664
7'	14'	239	6.0	2,858
7'	16'	321	8.0	3,080
7'	19'	403	10.0	3,330
9'	14'	300	7.8	3,996
9'	17'	450	11.3	4,773
9'	20'	590	14.8	5,162
9'	25'	855	21.4	5,994
9'	28'	1,000	25.0	6,327
9'	31'	1,130	28.5	6,605
12'	20'	870	21.8	8,880
12'	25'	1,345	33.6	10,101
12'	31'	1,825	45.6	11,544
12'	36'	2,300	57.5	12,432
12'	42'	2,780	69.5	13,653

ADD: PER SQUARE FOOT OF HEAVY DUTY CONCRETE SLAB \$ 4.94

NOTE: Above costs are based on <u>professional construction labor supervised by a contractor or his job foreman</u>.

For farm labor with no professional supervision, costs should be adjusted downward by 25 percent relative to the quality of the finished product.

GRAIN HANDLING SYSTEMS

Cost of handling equipment only does not include grain storage bins. Most grain handling systems are <u>professionally installed with contractor supervision</u>. In cases where unsupervised nonprofessional help such as farm labor is used, adjust the costs listed downward by 25 percent, depending on the quality of workmanship.

GRAIN LOADING AND UNLOADING SYSTEMS

CONVEYOR

DIAM	COST/LIN FT		
6"	\$ 75		
8"	102		
10"	133		
12"	183		
14"	211		
16"	266		

AUGER-TYPE

WIDTH	COST/LIN FT
12"	\$ 128
18"	200
24"	233
30"	272
36"	280

48"

BELT-TYPE



FEED MILL and COMPONENTS

372

ELECTRIC POWER PLANTS

HOME GENERATOR SETS

RATING - KW	GASOLINE	DIESEL
3.0	\$ 3,148	\$ 3,778
4.0	3,819	4,582
5.0	4,533	5,440
7.0	6,099	7,319

COMMERCIAL INDUSTRIAL GENERATORS

RATING - KW	GASOLINE	E DIESEL
10.0	\$ 14,	,500 \$ 18,00
12.5	17,	7,069 21,08
15.0	19,	23,41
20.0	21,	,820 27,19
25.0	22,	27,41
30.0	24,	,153 27,63
40.0	28,	33,26
50.0	31,	,623 36,78
60.0	41,	,485 48,55
100.0	51,	,346 60,32
150.0	69,	82,85

For Air Cooling, Deduct: 15%

For natural or LP gas fuel systems, Add per KW: \$ 25.46 For remote control starting, gasoline fuel, Add: \$ 97.59

NOTE: Above costs include minimal current load control switchboard facilities. Above costs do not include

ALTERNATING CURRENT LOAD CONTROL SWITCHBOARD

mounting pads

AUTOMATIC EMERGENCY SWITCHBOARD FOR GASOLINE PLANT

RAT	ľING		COST	RAT	TING		COST
KW	AMPS	VOLTAGE	EACH	KW	AMPS	VOLTAGE	EACH
15	130	240; 230/400	\$ 1,505	15	130	120/240	\$ 588
20	170	120/240; 240	2,134	20	170	120/240	1,980
25	210	240; 120/240	2,763	25	210	120/240	3,371
30	250	240; 120/240	3,392	30	250	120/240	4,763
40	330	120/240; 240	4,020	40	330	120/240	6,155
50	420	480;240	4,649	50	420	120/240	7,546
60	500	480;240	5,278	60	500	120/240	8,938
100	830	480;240	5,907	100	830	120/240	10,330

ADD FOR DIESEL POWERED PLANTS: \$ 187


FOR CIRCUIT BREAKERS: \$ 643 TO \$ 3,672

SCALES AND FUEL TANKS



LIVESTOCK SCALE with WOOD CAGE





BULK FUEL TANKS

LIVESTOCK SCALES

BEAM TYPE	SIZE	CAPACITY	(COST
FULL CAPACITY	14' X 8'	5 TON	\$	14,985
FULL CAPACITY	16' X 8'	10 TON		19,869
FULL CAPACITY	22' X 10'	15 TON		28,194

SCALE CAGES

	METAL			WOOD	
SIZE		COST	SIZE		COST
14'	\$	1,699	14' X 8'	\$	902
16'		1,909	16' X 8'		927
22'		2,636	22' X 10'		1,151
24'	-	2,871	24' X 10'		1,195

FOR TYPE REGISTERING BEAM, ADD. \$ 758 FOR PRINTER, ADD 1,565 FOR ELECTRONIC DIGITAL SCALE, ADD. 4,829

Scale pit 4 inch concrete walls and slab poured in place. May be poured in or on top of ground. If on top, compacted ramps and steps to scale beam included.

MOTOR TRUCK SCALES

SPECIFICATIONS

Reinforced concrete pit and platform. All steel structure and scale mechanism.

Motor truck scales are of two general types: the beam type (either manual or type registering) and the full automatic dial type. The construction of both, insofar as the weight carrying mechanism is concerned, is very similar. The method of recording the weights makes the difference.

CAPACITY	TOTAL COST
20 TONS	\$ 37,185
30 TONS	43,290
40 TONS	49,728
50 TONS	56,333
60 TONS	63,548
70 TONS	73,260

FOR WOOD PLATFORM, DEDUCT: 6%
FOR STEEL PLATE, ADD: 5%
FOR AUTOMATIC DIAL MODEL, ADD: \$ 2,831
FOR REMOTE READER-PRINTER, ADD: 9,324
FOR CARD PRINTER, ADD: 2,109

UNDERGROUND FUEL STORAGE

Costs are for complete installation and are based on <u>professional construction labor supervised by a contractor or his job foreman</u>. For farm labor with no professional supervision, costs should be adjusted downward by 25 percent relative to the quality of the finished product. For multiple installation, two or more tanks in one hole, deduct 7 percent for each extra tank, consider the largest tank as the base. <u>Costs do not include</u> electric pumps. See following page 8 in this section for pump costs.

GALLONS	COST	GALLONS	COST
300	\$ 6,334	4,000	\$ 16,368
550	7,287	5,000	18,722
1,000	9,585	6,000	22,086
2,000	12,444	8,000	24,888
3,000	14,014	10,000	30,158

ABOVE GROUND HORIZONTAL BULK (FUEL) STORAGE

Costs are for complete installation. Includes holding stand, discharge hose and valve. Does not include any electric pumps. See following Page 8 in this section for pump costs.

GALLONS	COST	GALLONS	COST
200	\$ 3,509	3,000	\$ 7,287
350	3,711	4,000	8,520
550	3,980	5,000	9,922
1,000	4,681	7,500	13,341
2,000	5,886	10,000	16,704

ELECTRONIC FUEL DISPENSERS

TYPE 1				
	WITHOUT METER	\$ 273	TO	\$ 698
	WITH METER	552	TO	874
TYPE II				
	WITHOUT METER	\$ 480	TO	\$ 1,262
	WITH METER	863	TO	1,512
TYPE III		\$ 835	TO	\$ 1,256
TYPE IV		\$ 1,222	TO	\$ 2,444
	•			
TYPE V		\$ 3,083	TO	\$ 3,980

NOTE: To calculate tank volume use the following formula: Volume in gallons = Pi x radius squared x length x 7.5.

EXAMPLE: A tank five feet in diameter and 14 feet in length; Pi equals 3.1416;

Radius (one half of diameter) equals 2.5 feet: 3.1416×2.5 squared x 14 feet x 7.5 = 2,062 gallons.

FUEL DISPENSERS







TYPE I—NO METER

TYPE I METER

TYPE II—WITH METER







TYPE III TYPE IV TYPE V

PREFABRICATED TELECOM / COMMUNICATION EQUIPMENT SHELTERS

Costs are for complete installation of <u>small prefabricated modular buildings</u> used for weather- and vandal-resistant equipment storage. Costs include a foundation and all wall, roof, and floor panels. Steel wall vents and entry door, and minimum electrical. Air conditioning and equipment power panel and wiring are not included.

SQUARE FOOT COSTS

CLASS	100	150	200	300	500	750
1	\$ 115.95	\$ 100.37	\$ 91.47	\$ 78.12	\$ 65.89	\$ 57.54
2	\$ 141.25	\$ 119.55	\$ 109.54	\$ 92.30	\$ 76.73	\$ 65.38
3	\$ 166.54	\$ 138.73	\$ 127.61	\$ 106.48	\$ 87.56	\$ 73.10

NOTE: For very low guality metal or fiberglass structures, reduce Class 3 costs by 55%.



PREFABRICATED EQUIPMENT SHELTER

TELECOM / COMMUNICATION EQUIPMENT SHELTERS



LOW QUALITY



AVERAGE QUALITY



GOOD QUALITY

2017-2018 RURAL BUILDING COST MANUAL

Section 7

COMPUTATIONAL TABLES

MENSURATION PRINCIPLES

PLANE FIGURE A plane surface bounded by either straight or curved lines having no thickness.

SOLID A body, such as a barrel, building, etc.

SQUARE MEASURE Area calculation requiring only two dimensions, length and width.

CUBIC MEASURECubic or cubage means volume and gives size in terms of its bulk. Calculation requires three dimensions:

length times width times depth or height or thickness.

WEIGHTS AND MEASURES

Tables of weights, measures and other information helpful to the assessor-appraiser.

METRIC MEASURE

Millimeter 0.001 meters
Centimeter 0.01 meters
Decimeter 0.1 meters
Meter 39.3685 inches

Kilometer 1,000 meters
Kilometer 0. 62137 miles
Meter 1.0935 yards
Meter 3.2807 feet
1 foot 0.30480 meter
1 foot 30.48 centimeters
1 inch 2.54 centimeters

LINEAR MEASURE

1 foot 12 inches

1 yard 3 feet, 36 inches

1 rod 5 1/2 yards, 16 1/2 feet, 25 links 1 furlong 40 rods, 220 yards, 660 feet

1 mile 8 furlongs, 320 rods, 1,760 yards, 5,280 feet

SURVEYOR'S LINEAR MEASURE

1 link 7.92 inches 1 rod 25 links

1 chain 4 rods, 100 links, 66 feet

1 furlong 10 chains

1 mile 8 furlongs, 80 chains

WEIGHTS AND MEASURES

SQUARE MEASURE

1 square foot 144 square inches

1 square yard 9 square feet, 1,296 square inches

1 square rod 1 pole or perch, 30 1/4 square yards, 272 1/4 square feet

1 rood 40 square rods, 1,210 square yards, 1/4 acre

1 acre 160 square rods, 4,840 square yards, 43,560 square feet

1 square mile 640 acres

SURVEYOR'S SQUARE MEASURE

1 square rod1 square chain1 acre625 square links16 square rods10 square chains

1 square mile 640 acres

CUBIC MEASURE

1 cubic foot 1,728 cubic inches, 7.481 gallons

1 cubic yard 27 cubic feet 1 cord foot 16 cubic feet

1 cord of wood 8 cord feet, 128 cubic feet

1 perch of masonry 24 3/4 cubic feet

1 bushel 1.2445 cubic feet

ANGLES AND ARCS

1 minute 60 seconds
1 degree 60 minutes
1 right angle 90 degrees, 1 quadrant
1 circumference 360 degrees, 4 quadrants

BOARD MEASURE

1 board foot length in feet times width in feet times thickness in inches

AREAS

Square feet of surface area equals square of one side multiplied by the given factor.

NUMBER

	OF	
REGULAR SHAPED	<u>SIDES</u>	FACTOR
Equilateral triangle	3	0.433
Pentagon	5	1.721
Hexagon	6	2.598
Heptagon	7	3.634
Octagon	8	4.828
Nonagon	9	6.182
Decagon	10	7.694
Undecagon	11	9.366
Dodecagon	12	11.196

MEASURES AND THEIR EQUIVALENTS

A gallon of water (U. S. Standard) weighs 8 1/3 pounds and contains 231 cubic inches.

A cubic foot of water contains 7 1/2 gallons, 1,728 cubic inches and weighs 62 1/2 pounds.

Doubling the diameter of a pipe increases its capacity four times.

To find the capacity of any size tank: given the dimensions of a cylinder in inches, to find its capacity in U. S. gallons; square the diameter, multiply by the length and by 0.0034. (Note: See table on tank capacities.)

Rectangular tanks: multiply the length by the width by the depth (all in inches) and divide the result by 231. The answer is the capacity in gallons.

Thirty one and one half (31 1/2) gallons water equals one barrel by weight.

British Thermal Unit (BTU) is the amount of the heat required to raise one pound of water one degree Fahrenheit.

A ton of refrigeration is measured by the displacement of the amount of heat required to melt a ton of ice in 24 hours. One motor horsepower of an electrically powered unit is normally required to produce one ton of refrigeration. Twelve thousand British Thermal Units (12,000 BTU) equals one ton.

Watts = Volts multiplied by Amps

Horsepower equals Kilowatts multiplied by 1.3405.

Kilowatts equal horsepower multiplied by 0.746.

WEIGHTS

BRICK: Common brick of the national size weigh from 4 1/2 to five pounds; pressed and paving brick, from six to seven pounds,

depending upon clay, burning and size.

LIME: On the basis of 53 pounds to the cubic foot, lime weighs about 66 pounds to the bushel, but in bulk it often sells on the basis

of 80 pounds to the bushel or 200 pounds to the barrel of 2 1/4 bushels.

MISCELLANEOUS WEIGHT AND MEASURE EQUIVALENTS

1 cubic inch of cast iron weighs 0.26 pounds

1 cubic inch of wrought iron weighs 0.28 pounds

1 cubic inch of water weighs 0.036 pounds

1 cubic foot of water weighs 62.321 pounds

1 United States gallon weighs 8.34 pounds

1 Imperial gallon weighs 10.00 pounds

1 United States gallon equals 231.01 cubic inches

1 Imperial gallon equals 277.274 cubic inches

1 cubic foot of water equals 7.48 U. S. gallons

1 gallon (water) weighs 8.34 pounds

1 gallon equals 0.1337 cubic feet

1 gallon equals 0.1074 bushels

1 cubic foot equals 0.8032 bushels

1 barrel (oil) equals 42 gallons

1 barrel (water) equals 31.5 gallons

A span is 9 inches

A hand, horse measurement, equals 4 inches

A knot, nautical, equals 6,080.27 feet

A fathom, nautical, equals 6 feet

A stone equals 14 pounds

Pressure in pounds per square inch of column of water equals 0.434 times the height of the column in feet.

A square acre measures approximately 208.7 feet on each side.

1 acre measures about 8 rods by 20 rods, or any two combinations of rods whose product equals 160.

MISCELLANEOUS WEIGHT AND MEASURE EQUIVALENTS

To convert bushels to tons, multiply number of bushels by 60 and divide the product by 2,000 (average maximum weight of commodities 60 pounds per bushel).

To convert gallons to bushels, divide gallons by 9.35. Answer in bushels.

To convert cubic measure into bushels, multiply by 0.8035.

AREAS AND MEASUREMENTS

To find the circumference of a circle, multiply the diameter by 3.1416.

To find the diameter, multiply circumference by 0.3183 or divide circumference by 3.1416.

To find the radius, multiply circumference by 0.15915.

To find the side of an inscribed square, multiply the diameter by 0.07071 or multiply the circumference by 0.2251.

To find the side of an equal square, multiply the diameter by 0.8863 or multiply the circumference by 0.2821.

SQUARE: A side multiplied by 1.4142 equals the diameter of its circumscribing circle.

A side multiplied by 4.443 equals the circumference of its circumscribing circle.

A side multiplied by 1.126 equals the diameter of an equal circle.

A side multiplied by 3.547 equals the circumference of an equal circle.

To find the area of a circle, multiply the circumference by one-quarter of the diameter or multiply the square of the diameter by 0.7854 or multiply the square of the circumference by 0.07958 or multiply the square of one-half of the diameter by 3.1416.

To find the surface of a sphere or globe, multiply the diameter by the circumference or multiply the square of the diameter by 3.1416 or multiply four times the square of the radius by 3.1416.

To find tank capacities, diameter square times .0034 equals gallons per inch of height - Base 42 gallons per barrel.

To find area of a triangle, multiply base by 1/2 perpendicular height.

To find area of an ellipse, product of both diameters times 0.7854.

To find area of a parallelogram, base times altitude.

To find cubic inches in a ball, multiply cube of diameter by 0.5236.

To find cubic contents of a cone, multiply area of base by one third the altitude.

Area of rectangle equals length multiplied by width.

Surface of frustum of cone or pyramid equals sum of circumference of both ends times 1/2 slant height plus area both ends.

Contents of frustum of cone or pyramid: multiply area of two ends and get square root, add the two areas and times 1/3 altitude.

CONVERSION TABLES
TABLE FOR AREA AND CAPACITY OF CIRCULAR TANKS / FOOT

DIAMETER	CIRCUMFRENCE	AREA	GALLONS		BARRELS (OIL)
3	9.42	7.07	53	6	1.26
4	12.57	12.57	94	10	2.24
5	15.71	19.63	147	16	3.50
6	18.85	28.27	212	23	5.00
7	21.99	38.48	288	31	6.80
8	25.13	50.27	376	42	9.00
9	28.27	63.62	477	51	11.30
10	31.42	78.54	587	63	14.00
11	34.56	95.03	711	76	16.90
12	37.69	113.10	846	91	20.20
13	40.84	132.73	993	107	23.70
14	43.98	153.94	1,151	124	27.40
15	47.12	176.72	1,322	142	31.50
16	50.26	201.06	1,054	162	35.80
17	53.41	226.98	1,698	182	40.40
18	56.55	254.47	1,903	204	45.30
19	59.69	283.53	2,121	228	50.50
20	62.83	314.16	2,350	252	56.00
21	65.97	346.36	2,591	278	61.70
22	69.12	380.13	2,843	305	67.70
23	72.26	415.48	3,108	334	74.00
24	75.40	452.39	3,384	364	80.60
25	78.54	490.87	3,672	394	87.40
26	81.68	530.93	3,971	427	94.60
27	84.82	572.56	4,283	460	102.00
28	87.97	615.75	4,606	495	109.70
29	91.11	660.52	4,941	531	117.60
30	94.25	706.86	5,287	568	125.80
31	97.39	754.77	5,646	606	134.40
32	100.53	804.25	6,016	646	143.20
33	103.67	855.30	6,398	687	152.30
34	106.81	907.92	6,791	730	161.60
35	109.96	962.11	7,197	773	171.30
36	113.10	1,017.88	7,614	818	181.30
37	116.24	1,075.21	8,043	864	191.50
38	119.38	1,134.11	8,483	911	202.00
39	122.52	1,194.59	8,936	960	212.70
40	125.66	1,256.64	9,400	1,010	223.80

NOTE: Capacity of cylindrical tanks standing on end.

CONVERSION TABLES

NOTES on cylindrical tanks: To find the capacity in cubic feet of a round tank or cistern, multiply the square of the average diameter by the depth and multiply the product by 0.785.

TABLE FOR CONVERSION OF LINEAR FEET INTO BOARD FEET

2 by 4	0.667 board feet
3 by 4	1.000 board feet
2 by 6	1.000 board feet
2 by 8	1.333 board feet
2 by 10	1.667 board feet
2 by 12	2.000 board feet
2 by 14	2.333 board feet
2 by 16	2.667 board feet
3 by 6	1.500 board feet
4 by 6	2.000 board feet
4 by 10	3.333 board feet
4 by 12	4.000 board feet
6 by 6	3.000 board feet
6 by 8	4.000 board feet
10 by 12	10.000 board feet
12 by 12	12.000 board feet

BOARD MEASURE

Multiply thickness in inches by width in inches, divide product by 12 and multiply result by the length in feet. The result is board measure content.

EXAMPLE

Two inches times 10 inches equal 20 square inches divided by 12 equals 1.667 board feet times 1,000 linear feet equals 1,667 board feet.

^{*}To find the capacity in barrels (oil) equals diameter squared times 0.1399 times height.

^{**} To find the capacity in gallons equals diameter squared times 5.8748 times height.

CENTER PIVOT IRRIGATION SYSTEM DATA

-----AREA COVERED IN ACRES -----

TOTAL SYSTEM LENGTH (IN FEET) <u>2</u> /	PERCENT OF WATER APPLIED IN LAST 100 FEET 1/	TOTAL ACRES OF SQUARE FIELD TWICE LENGTH OF SYSTEM	WITH GUN <u>3</u> / SPRINKLER CORNERS USED ONLY	WITH GUN SPRINKLER USED ON ENTIRE CIRCLE <u>3</u> /	WITHOUT END GUN
600	30.6	33.1	30.8	35.3	26.0
650	28.4	38.8	36.0	40.6	30.5
700	26.5	45.0	41.5	46.2	35.3
750	24.9	51.7	47.3	52.1	40.6
800	23.4	58.8	53.4	58.4	46.2
850	22.1	66.3	59.8	65.1	52.1
900	21.0	74.4	66.5	72.1	58.4
960	19.9	82.9	73.6	79.5	65.1
1,000	19.0	91.8	81.1	87.3	72.1
1,050	18.1	101.2	89.0	95.4	79.5
1,100	17.4	111.1	97.3	103.8	87.3
1,150	16.6	121.4	106.0	112.7	95.4
1,200	16.0	132.2	115.1	121.9	103.9
1,250	15.4	143.5	124.6	131.4	112.7
1,300	14.8	155.2	134.5	141.4	121.9
1,320	14.6	16.0	138.5	145.4	125.7
1,350	14.3	167.4	144.7	151.6	131.4
1,400	13.8	180.0	155.4	162.3	141.4
1,450	13.3	193.1	166.5	173.3	151.6
1,500	12.9	206.6	178.0	184.6	162.3

^{1/} Less volume of end gun when used.

EXAMPLE: System is 900 feet long. Then 21 percent of water is applied in last 100 feet; 66.5 acres are covered with gun used in corners only.

<u>2/</u> Generally outside drive wheel is approximately 50 feet from end.

<u>3/</u> Based on 100 feet gun coverage.